

# ER14250 3.6V 1250 mAh / 3PT

# **Lithium Battery**

# Non-Rechargeable Images

✓	Nominal Capacity :  Discharged Capacity at 1mA,+25°C, 2.0V Cut off	1250 Mah
✓	Open Circuit Voltage:	3.65V
✓	Maximum Recommended Continuous Current : Discharged to 2.0V at + 25°C permitting %50 of the nominal ca achieved	25Mah apacity to be
✓	Max. Pulse Capability: 100Mah D100Mah, 0.1 second pulses every 2 min, drained with %50, 1mA at 25°C from Dundicharged cells with 20uA base current, yield voltage readings above 2.7V, the value may vary according to the pulse charecteristics, the temperature and the cell's previous histroy	
✓	Operating Temperature Range:	-55°C+85°C





#### **Benefits**

- ✓ High voltage, stable during most of the application's lifetime
- ✓ Wide operating temperature range
- ✓ Low self-discharge rate (less than 1 % per year of storage at + 20°C)
- ✓ Easy integration into compact systems
- ✓ Superior resistance to atmospheric corrosion


### **Key features**

- ✓ Stainless steel container and end caps (low magnetic signature)
- ✓ Hermetic glass-to-metal sealing
- ✓ Non-flammable electrolyte
- ✓ Compliant with IEC 86-4 safety standard and IEC 60079-11 intrinsic safety standard
- ✓ Underwriters Laboratories (UL) Component Recognition (File Number MH 12609)
- √ Non-restricted for transport

#### Main applications

- ✓ Utility metering
- ✓ Automatic meter reading
- ✓ Alarms and security devices
- ✓ Memory back-up
- Computer real-time clocks
- ✓ Tracking systems
- ✓ Automotive electronics
- ✓ Professional electronics


#### **Technical Drawing**




Dimensions in mm Weight:9g



#### Typical Discharge Characteristics at 25°C



# **Voltage and Temperature Curve**



## Capacity and Current Curve (Cut off with 2.0V)

