

### 1. Identification of the substance/preparation and of the company / undertaking

Product name: Lithium Primary Battery

Product Designation: Lithium Thionyl Chloride Battery Li-SOCl<sub>2</sub>/ **All ER Type Batteries**

Nominal Voltage: 3.6V

Chemical system: Lithium/ Thionyl Chloride Battery Li-SOCl<sub>2</sub>

Designed for recharge: Yes No

Company name: Power-Xtra Groupe Limited Battery Co., Ltd.

128 Xingguang Road, Hi-Tech Park China

Tel: +86 574 87491087 / 87493214

Fax: +86 574 87493903

### 2. Hazards identifications

For the battery cell, chemical materials are stored in a hermetically sealed metal case, designed to withstand temperatures and pressures encountered during normal use. As a result, during normal use, there is no physical danger of ignition or explosion and chemical danger. However, do not open, short-circuit, squeeze, burn, disassemble, expose to flame, mix different models, different chemical properties or different types of batteries.

The battery cell case will be breached at the extreme, hazardous materials may be released.

Most important hazard and effects

Human health effects:

Inhalation: The steam of the electrolyte has an anesthesia action and stimulates a respiratory tract.

Skin contact: The steam of the electrolyte stimulates a skin. The electrolyte skin contact causes a sore and stimulation on the skin.

Eye contact: The steam of the electrolyte stimulates eyes. The electrolyte eye contact causes a sore and stimulation on the eye. Especially, substance that causes a strong inflammation of the eyes is contained.

Environmental effects: Since a battery cell remains in the environment, do not throw out it into the environment.

### 3. Compositions /Information on Ingredients

Chemical Nature: Lithium/ Manganese dioxide batteries

Ingredient name	CAS No.	Wt%
Litium	7439-93-2	3.5 -5.0
Thionyl Chloride	7719-09-7	40-45
Tetrafluoroethylene	9002-84-0	0.02
Aluminum Chloride	7446-70-0	1-5
Carbon	7782-42-5	3.0-4.0

### 4. First-aid measures

Apply to leak out of the material from inside the Lithium Thionyl Chloride Batteries.

4.1. General advice: Show this safety data sheet to the doctor in attendance. After receiving the first-aid measure required, consult a physician if necessary.

4.2. Skin contact: Remove contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If chemical burns or skin sustained stimulation, consult a physician immediately

4.3. Eyes contact: Check for and remove any contact lenses. Get medical attention. Immediately flush eyes with running water for at least 30 minutes, disappear until the chemical residues so far, keeping eyelids open. Provide a readily-accessible eyewash facility and quick-drench safety shower. Do not rubbing eyes with hand.

4.4. Inhalation: Move exposed person to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

4.5. Ingestion: Wash out mouth with water. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

4.6. Most important symptoms and effects, both acute and delayed: See Section 2 and Section 11 for more information.

4.7. Immediate / special treatment: Symptomatic treatment and supportive therapy as indicated. Following severe exposure the patient should be kept under medical review for at least 48 hours.

### 5. Fire-fighting measures

5.1. Extinguishing media: In case of fire, water flooded ground fire. If the battery is burning, water may not be extinguished, but can use water cooling adjacent batteries so as to control the spear of fire. The preferred medium for small fire is carbon dioxide, dry powder, or foam extinguishing agent, but for the lithium battery is burning may be no use, the battery will burn until complete combustion. In fact, all lithium batteries can be controlled by water. However, when using water to produce hydrogen gas may be mixed with air to form explosive mixture.

LITH-X (graphite powder) or copper powder fire extinguishers, sand, dry, powdered dolomite or soda can be used as smothering agent

5.3. Special hazards arising from the substance or mixture: In combustion emits toxic fumes, metallic oxides.

5.4. Advice for fire-fighter: Firefighters must wear self-contained breathing apparatus, wear full body fire suit, fire extinguishing in the upwind. As far as possible will be transferred to empty containers from the scene. Keep the fire water spray container cooling, until the end of fire.

### 6. Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapors or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions: Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3. Collecting, clearing method and disposal material: Small spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13).

Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see section 1 for emergency contact information and section 13 for waste disposal. Local waste disposal regulations must be followed

## 7. Handling and Storage

7.1. Precautions for handling: If the Lithium Thionyl Chloride Battery gives off an odor, generates heat, becomes discolored or deformed, or in any way appear abnormal during use, recharging or storage, immediately remove it from the device and stop using. Don't put the battery excessive vibration, avoid short circuit, however accidental short circuit for a short period of time will not have a serious impact on the battery. Long-term short circuit can make Lithium Thionyl Chloride Battery loss of energy, generate a lot of heat burn skin, and even cause a fire or explosion. Chaos of the battery in bulk in containers, coins, metal accessories, metal workbench, covered by or metal belt and so on Lithium Thionyl Chloride Battery device can be used for assembly is the source of cause a short-circuit. Transport or storage Lithium Thionyl Chloride Battery should have effective measures of prevent short circuit. Don't disassembly or damage to the battery. Away from heat, sparks, open flames and hot surfaces.

7.2. Precautions for storage: Stored in a cool, dry and ventilated place, may cause the Lithium Thionyl Chloride Battery performance loss under high temperature, leakage, rust. Don't expose the Lithium Thionyl Chloride Battery under the open flame, stored away from moisture.

## 8. Exposure Controls/ Personal Protection

8.1. Exposure limit: Thionyl Chloride: ACGIH TLV-CL 4.9 mg/m<sup>3</sup> (1 ppm); Aluminum Chloride: CGIH TLV-TWA 2 mg(Al)/m<sup>3</sup>.

8.2. Engineering control: Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and

safety showers are close to the workstation location. Use explosion-proof electrical / ventilating / lighting / equipment. Set up emergency exit and necessary risk-elimination area.

8.3. Respiratory protection: If the batteries leaks must try to keep the air circulation, avoid operating in a narrow place.

In the normal use conditions of use respiratory protective equipment is not necessary. Respiratory protection may be required under exceptional circumstances when excessive air contamination exists.

8.4. Eye protection: Not necessary under normal use conditions, if the battery damaged or leaking. Wear goggles/safety glasses giving complete eye protection.

8.5. Skin and body protection: Not necessary under normal use conditions, if the battery damaged or leaking wear appropriate clothing to minimize skin exposure.

8.6. Hand protection: Not necessary under normal use conditions, if the battery damaged or leaking wear appropriate protective gloves

8.7. Other protection: Do not eat, drink or smoke in the workplace. Shower and change clothes after work. Observe the common precautionary measures, contaminated clothes must be changed immediately. Wash hands after work is completed.

## 9. Physical and Chemical Properties

Appearance: Battery state under normal temp: Solid

pH value (Specify the concentration): No data

Color: N/A

Odor: N/A

Solubility: Insoluble in water.

Flammability: Non flammability

Melting point: No data

Explosion: Not explode

## 10. Stability and Reactivity

10.1. Stability: Stable under normal conditions of use, storage and transport.

10.2. Reactivity: Under the condition of burning may produce harmful breakdown products

10.3. Incompatible materials: Strong oxidizing agents.

10.4. Conditions to avoid: In contrast to the nature of the material, overheating, exposed to damp air or water, mechanical vibration and power abuse.

10.5. Hazardous decomposition products: Hazardous decomposition products formed under the condition of burning .

- Metal oxide, or smoke etc.

## 11. Toxicological Information

11.1. Acute toxicity: Aluminum Chloride: Oral-rat LD50: 3450mg/kg, Oral-rat LD50: 1130mg/kg.

11.2. Skin corrosion/irritation: Aluminum Chloride, Lithium: Skin corrosion / irritation (Category 1B).

Thionyl Chloride: Skin corrosion / irritation (Category 1A).

11.3. Eye corrosion/irritation: Aluminum Chloride, Thionyl Chloride, Lithium: Eye damage / eye irritation (Category 1).

11.4. Respiratory or skin sensitization: According to the existing data, the product is not classified.

11.5. Germ cell mutagenicity: According to the existing data, the product is not classified.

11.6. Carcinogenicity: According to ACGIH, IARC, NTP is not listed as a carcinogen.

11.7. Reproductive toxicity: According to the existing data, the product is not classified.

11.8. Specific target organ toxicity -single exposure: May cause respiratory irritation.

11.9. Specific target organ toxicity - repeated exposure: According to the existing data, the product is not classified.

11.10. Aspiration hazard: According to the existing data, the product is not classified.

## 12. Ecological Information

12.1. Ecotoxicity values: Aluminum Chloride: Toxicity to fish LC50: 6.17 mg/l (96h);

Crustacean animal EC50: 1.9mg/l (48h); Algae / aquatic plants ErEC50: 0.515mg/l (96h).

12.2. Persistence and degradability: No further relevant information available.

12.3. Bioaccumulative potential: No further relevant information available.

12.4. Mobility in soil: No further relevant information available.

12.5. Other adverse effects: Without government permission, do not dispose directly into rivers, watercourses or drains..



### 15. Regulatory Information

#### 15.1. Domestic chemical inventory

CAS No.	(1)	(2)	(3)	(4)	(5)	(6)
7439-93-2	Listed	Not Listed	Listed	Not Listed	Not Listed	Not Listed
7782-42-5	Not Listed					
9002-84-0	Not Listed					
7719-09-7	Listed	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
7446-70-0	Listed	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed

- [1] 《Catalog of Hazardous Chemicals(2015 Edition)》
- [2] 《Highly toxic chemicals directory》
- [3] 《Dangerous chemicals directory used to manufacture exploder》
- [4] 《National dangerous wastes directory》 annex A
- [5] 《Strict limits on the import and export of toxic chemicals directory in China》
- [6] 《List of Import and Export of Controlled ODS in China》

#### 15.2. International chemical inventory

CAS No.	TSCA	EINECS	DSL	IECSC	NZIoC	PICCS	KECI	AICS
7439-93-2	Listed	Listed	Listed	Listed	Listed	Listed	Listed	Listed
7782-42-5	Listed	Listed	Listed	Listed	Listed	Listed	Listed	Listed
9002-84-0	Listed	Not Listed	Listed	Listed	Listed	Listed	Listed	Listed
7719-09-7	Listed	Listed	Listed	Listed	Listed	Listed	Not Listed	Listed
7446-70-0	Listed	Listed	Listed	Listed	Listed	Listed	Listed	Listed

TSCA: United States Toxic Substances Control Act Inventory

EINECS: European Inventory of Existing Commercial Chemical Substances

DSL: Canadian Domestic Substances List

IECSC: China Inventory of Existing Chemical Substances

PICCS: Philippines Inventory of Chemicals and Chemical Substances

NZIoC: New Zealand Inventory of Chemicals

KECI: Existing and Evaluated Chemical Substances

AICS: List of existing chemical substances in Australia

### 16. Other Information

16.1. Legal disclaimer: The above information is believed to be correct but we can not guarantee the absolute universality and accuracy and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. The above-named supplier and its affiliates shall not be held liable for any damage resulting from handling or from contact with the above product.