

Model: Power-Xtra PX4000WB4S - 4S1P - 14.8V 4000 mAh Li-Polymer Battery - 60C

Stock Code: 900.630.503.015

Item	Specifications	Conditions
Nominal Voltage	14.8V±0.05V	0.2C Discharge
Charging	Method	CC-CV
	Voltage	16.8V±0.05V
Typ. Capacity	4.000 mAh	0.2C Discharge cut-off Voltage 12.0V after standard charge at 23±2°C
Maximum Charge Voltage	16.8V	4.2V/Cell
Configuration	4S1P	
Standard Charging Current	800 mA	0.2C
Standard Discharging Current	2.000 mA	0.5C
Maximum Charging Current	20 AH	5.0C
Max. Constant Discharge Current	240 AH	60.0C - Ref.Temperature:10-50°C
Max. Burst Discharge Current	480 AH	120.0C ≤3S
Discharge Cut-Off Voltage	12.0V	
Temperature	Charge	0 to +10°C
		10 to +45°C
	Discharge	-20 to +60°C
	Storage	Less than 1 year: -20-25°C
		less than 3 months: -20-30°C
		less than 1 months: -20-45°C
Weight	480 gr	approximately
Cycles Test	Measure capacity under the cycle conditions described below, until the discharge capacity ≤80% for three times. Cycle conditions: Standard Charge (CC-CV, 1300mA, 16.8V) , Rest for 30min;Discharge with 1C, 12.0V cutting off. Testing temperature is 23±2°C Cycle Life≥500 cycles	

Model: Power-Xtra PX4000WB4S - 4S1P - 14.8V 4000 mAh Li-Polymer Battery - 60C
Stock Code: 900.630.503.015

Item	Description	Dimension
T	Thickness	33.0± 1.0 mm
W	Width	45.0± 2 mm
L	Length	135.0± 2 mm
BP	Balance Plug	JST-XH
DP	Discharge Plug:	XT90

Image

