


Model: Power-Xtra PX420XL2S - 2S1P - 7.4V 420 mAh Li-Polymer Battery - 25C

Stock Code: 900.869.503.303

Item	Specifications	Conditions
Nominal Voltage	7.4V±0.05V	0.2C Discharge
Charging	Method	CC-CV
	Voltage	8.4V±0.05V
Typ. Capacity	420 mAh	0.2C Discharge cut-off Voltage 3.0V after standard charge at 23±2°C
Maximum Charge Voltage	8.4V	4.2V/Cell
Configuration	2S1P	
Standard Charging Current	420 mA	1.0C
Standard Discharging Current	420 mA	1.0C
Maximum Charging Current	840 mA	2.0C
Max. Constant Discharge Current	3.150 mA	7.5C - Ref.Temperature:10-50°C
Max. Burst Discharge Current	6.300 mA	15.0C ≤3S
Discharge Cut-Off Voltage	6.0V	
Temperature	Charge	0 to +10°C
		10 to +45°C
	Discharge	-20 to +60°C
	Storage	Less than 1 year: -20-25°C
		less than 3 months: -20-30°C
		less than 1 months: -20-45°C
Weight	47 gr	approximately
Cycles Test	Measure capacity under the cycle conditions described below, until the discharge capacity ≤80% for three times. Cycle conditions: Standard Charge (CC-CV, 0.2C, 4.2V) , Rest for 30min;Discharge with 1C, 3.0V cutting off. Testing temperature is 23±2°C Cycle Life≥500 cycles	

Model: Power-Xtra PX420XL2S - 2S1P - 7.4V 420 mAh Li-Polymer Battery - 25C
Stock Code: 900.869.503.303

Item	Description	Dimension	Technical Drawing
T	Thickness	19.0± 0.2 mm	
W	Width	24.0± 1 mm	
L	Length	45.0± 1 mm	
BP	Balance Plug	JST-XHP-3	
DP	Discharge Plug	XT30U	

Image

