

**Model:** PX224147 - 3.0V 800 mAh - Prismatic

**Stock Code:** 900.869.503.369

Item	Specifications	Conditions
Open circuit voltage	3.1V	0.2C Discharge
Nominal capacity	800mAh	(At +25°C, battery discharged at continuous current 1mA until voltage reaches cut-off voltage 2.0V. The capacity can vary at different temperature, discharge current or cut-off voltage.)
Maximum continuous current	200 mA	(At +25°C, 2.0V cut-off, battery discharged for minimum 50% of rated capacity.)
Maximum pulse discharge current	400 mA	(At +25°C, 2.0V cut-off, battery discharged for minimum 50% of rated capacity with max pulse for 3 seconds after 27 seconds break. The discharged capacity may vary according to the pulse characteristics, the temperature, and the cell's previous history. Fitting the cell with a capacitor may be recommended in severe conditions, consult Power-Xtra.)
Storage	Recommended	<p>Less than 1 year: -20~30°C</p> <p>Less than 3 months: -20~35°C</p> <p>Less than 1 months: -20~45°C</p>
Operating temperature range	-40°C~+70°C	
Weight	6.5 gr	approximately
Li metal content	0.26g	

**Model:** PX224147 - 3.0V 800 mAh - Prismatic

**Stock Code:** 900.869.503.369

Item	Specifications	Representative Image
Thickness	$2.3 \pm 0.5\text{mm}$	
Width	$43.0\text{mm} \pm 1\text{mm}$	
Length	$49.0\text{mm} \pm 1\text{mm}$	