

Power-Xtra CR3032-1F2YV - 3V Lithium Li-MnO2 Battery - 2 Pins - Horizontal -119

SPECIFICATIONS OF SINGLE CELL

Type Li-Mn02 Buton with Pins

Stock 900.600.503.137

Model CR3032, CR-3032, PX-CR3032-1F2

TECHNICAL INFORMATIONS

| Item | Specifications | Conditions | |
|--|----------------|---|--|
| Nominal Voltage | 3.0V | | |
| Typical Capacity | 580 mAh | Standard discharge with load 7.5k Ω | |
| Off-load voltage | ≥3.20 V | No load | |
| Typical Weight | 4.75 gr | | |
| Recommended Storage Temperature Range | 20+/-2°C | 5 years after delivery under proper storage conditions. | |
| Recommended Operation Temperature Range | -20° C to 60°C | | |
| Shelf Life | 5-7 Years | Recommended Storage Range : 20+/-2°C Recommended Humidity Range : 65+/-20%RH | |

Image and Technical Drawings

| Image | Technical Drawing | STANDARD | |
|---|---|----------|----------------|
| Lith H Lith M Cell CR3032 31 32 32 | | Diameter | 30.0 (-0.2) mm |
| | € -5- 2,6- 2,6- 0 1 -3,8 0 1 +-5±0,5 | Height | 3.8 (±0.1) mm |

REV001-Revised Date:25.12.2021

www.power-xtra.com