power-xtra

Model: Power-Xtra PX224147 - 3.0V 800 mAh Li-MnO2 Lithium Battery / Non-Rechargeable Stock Code: 900.869.503.369

TECHNICAL INFORMATIONS			
ltem	Specifications	Conditions	
Open circuit voltage	3.1V	0.2C Discharge	
Nominal capacity	800mAh	(At +25°C, battery discharged at continuous current 1mA	
		untilvoltage reaches cut-off voltage 2.0V. The capacity can	
		vary atdifferent temperature, discharge current or cut-off	
		voltage.)	
Maximum continuous	200 mA	(At +25°C, 2.0V cut-off, battery discharged for minimum 50%	
current		of rated capacity.)	
Maximum pulse discharge current	400 mA	(At +25°C, 2.0V cut-o, battery discharged for minimum 50%	
		of rated capacity with max pulse for 3 seconds after 27	
		seconds break. The discharged capacity may vary according	
		to the pulse characteristics, the temperature, and the cell's	
		previous history. Fitting the cell with a capacitor may be	
		recommended in severe conditions, consult Power-Xtra.)	
Storage (recommended)	Storage	Less than 1 year: -20~30°C	Ctoroco
		less than 3 months: -20~35°C	Storage (recommended) -+30°C
		less than 1 months: -20~45°C	
Operating temperature	Operating	40%	
range	temperature range	-40°C~+70°C	
Weight	6.5 gr	approximately	
Li metal content	0.26g		

MAIN APPLICATIONS

- Security System
- Smart Metering
- RFID and Tracking System
- Wireless Transmitting
- Smart Home Devices
- Military Devices

BENEFITS

• High Voltage Response, Stable During Most of the Lifetime of the Application

- Energy Density up to 830Wh/L
- Wide Operating Temperature Range (-40°C~+70°C)
- Low Self-discharge Rate (less than 1% per year
- after 1 year of storage at +25?)

REV001:18.12.2024


power-xtra

Model: Power-Xtra PX224147 - 3.0V 800 mAh Li-MnO2 Lithium Battery / Non-Rechargeable Stock Code: 900.869.503.369

Dimension Details

ltem	Description	Dimension
Т	Cell Tab Thickness	2.3± 0.5 mm
W	Cell Tab Width	43.0± 1 mm
L	Cell Tab Length	49.0± 1 mm
CL	Cable Length Length	
Р	Connector Model	

Technical Drawing



Dimensions in mm

REV001:18.12.2024